

>> Intelligent multi-document handling  
for front-office applications

## Passbook - Transactional Printers



# PR90 Plus

The new PR90 Plus redesigned to offer the ultimate performance in its category combined with the best ergonomics to fit in the busiest front desks for tellers in bank branches or any industry where fast transaction safe print is a must.

### VALUE AND QUALITY FEATURES

- Print speeds reaching 684 characters per second (in 12 cpi mode)
- New redesigned flat low cover for better space management
- Unique 2 lines x 20 chars display for clear and comprehensive messages
- Passbook and cut sheet
- Improved connectivity with multiple easy to install interface choices
- User friendly interface
- 24-wire print head for high print quality
- Print head life of 600 million dots/needle (400 M character)
- Improved MICR support (option)
- Ideal for banks, post offices, travel agencies, public administration, healthcare, transportation and insurance companies

#### Performance at your fingertips

The PR90 Plus has been designed to meet the most demanding performance requirements. With print speed reaching 684 characters per second the PR90 Plus is by far the fastest transactional printer on the market today.

#### Superior build quality

The PR90 Plus is built to last and offers the highest level of service. Each component of the printer is built to the highest industry standard. A new redesigned cover with flat top surface and lower height allows better fitting into space restricted counters. The print head design with special needles made of Tungsten carbide offers high quality, precision and improved life span. The precise mechanism ensures best in class paper handling and highest print quality.

#### Feature rich printer

Built with the ease of use in mind, the PR90 Plus manipulation is a snap. It is equipped with an LCD that displays 2 lines of 20 characters each, unique in its category, a user friendly interface and enough buttons to operate the printer with utmost simplicity. Its unique design allows easy access for maintenance and ribbon change.

When it comes to connectivity, the PR90 Plus is distinguished with its extreme flexibility. With space to account for optional parallel interface, dual serial ports, USB, and LAN, PR90 Plus satisfies all your environment needs.

**globalis**  
international

[www.globalis.com](http://www.globalis.com)

Print technology	24-pin, continuous form serial impact dot matrix
Print speed	DRAFT DP NLQ LQ 10 cpi 570 cps 414 cps 207 cps 140 cps 12 cpi 684 cps 497 cps 248 cps 168 cps
Character sets	ISO 8859/1-9, ISO 8859/15, Olivetti code tables (7bit & 8bit), Code Pages 210, 220, 437, 850-858, 860-866, 1250-1257, Epson Ext. Char Set in 13 national versions, IBM 864, PC 4352 (Arabic)
Character attributes	Bold, underline, overline, sub/superscript, double width, double height, double width and height, horizontal and vertical expansion, italic
Fonts	Arabic, Roman, Sans Serif, Italic, OCR-A, OCR-B, Chinese and other national character sets
Bar codes	Interleaved 2/5, Industrial 2/5, EAN-8, EAN-12, Code 39, 128, Codabar, UPC/A, UPC/E
Print characteristics	Character spacing: 5, 10, 12, 12.9, 15, 16.6, 17.1, 18, 20, 30 cpi Line spacing: 6, 8, lpi, n/60, n/72, n/180, n/216, n/360 per inch Print line length: 94 characters @ 10 cpi
Resolution	360 x 360 dpi (HxV)
Paper handling	- Cut sheet and passbooks from front - Automatic document alignment - Automatic document edge sensing - Automatic pressure adjustment depending on paper thickness Passbook specifications: thickness: max. 2.0 mm; width: 110 mm - 241 mm Single Sheet Width: 80 - 245 mm Single Sheet Weight: 30 to 160g/m <sup>2</sup> ; Formsets up to 240 g/m <sup>2</sup> Copies: 1 original + 6 copies
Emulation	IBM® Proprinter II / X24; IBM® 9068; Epson® LQ 1600K; Olivetti PR2E/PR40+; OKI 5530SC
Interface and connectivity	Standard: Serial RS-232 Additional Options: Parallel IEEE 1284 / Parallel + USB 2.0 / 2nd Serial RS-232 / USB 2.0 / 2nd Serial RS-232 + USB 2.0 / LAN
Optional devices	Magnetic strip reader/writer MICR reader Scanner
Input data buffer	64 K
Memory	16 MBytes
Diagnostics	Selftest, hexdump, remote diagnostics via interface, Unique ID-number
Reliability	MTBF: 10,000 hours @25% duty cycle
Consumables	Type: Black ribbon cartridge; Life: 7 million characters (10 million characters available)
Print head life	> 600 million dots/needle (400 Million characters)
Physical	Dimensions (w x d x h): 398 x 296 x 201 mm; Weight: 9 kg
Operating environment	Temperature: 5° to 35° C Relative humidity: 15-85% Acoustics: <54 dBA Voltage: 110V +/- 10% and 240V +/- 10% Frequency: 50 - 60 Hz Power consumption: 170W, 11W Standby
Regulatory	VDE/GS, UL, CE, CCC, FCC-B
Warranty	Standard one-year

### Contact Information

**Canada** 2345 Michelin, Suite 210 - Laval, Québec, Canada H7L 5B9 Tel.: (450) 686-9981 | Fax: (450) 686-9962 | info-canada@globalis.com

**Gulf, Pakistan & CIS** Al-Khaleej Bldg., Office 307, Zabeel Road - P.O. Box: 52460, Dubai, U.A.E. - Tel.: (971-4) 334-6700 | Fax: (971-4) 334-6912 | info-dubai@globalis.com

**Egypt** Nasr City, Cairo 40 Alef of Samir Abdel Raouf Street (Ext. of Makram Abaid) - Floor No. 9 - Flat No. 91 | Floor No.10 - Flat No. 101 - Tel. : (02) 22 73 53 38 - (02) 22 70 28 54 Fax: 02) 22 70 28 54 info-egypt@globalis.com

**Saudi Arabia** Riyadh - Olaya Street | behind Al Moussa Building P.O. Box: 55736 Riyadh 11544 - Tel.: (966-1) 2150122 | Fax: (966-1) 2150664 | info-saudi@globalis.com

**Levant, Iran, Maghreb & Turkey** Garden Tower, Office 9A, Antelias, Beirut - Lebanon Tel.: (961) 4 41 42 48 | Fax: (961) 4 41 48 42 | info-maghreb@globalis.com - info-beirut@globalis.com

**Central America** Calle Antigua a San Antonio Abad, Pasaje Carolina #20 - San Salvador, El Salvador, Centro America. Tel: (503) 2542-0732 - (503) 7696-906 info-elsalvador@globalis.com

PR90 Plus with Serial & Parallel/Serial/USB option



**globalis**  
international

[www.globalis.com](http://www.globalis.com)