


CF40

Continuous Forms Laser Printer

High Performance and Low Printing Cost

- Demanding Media like plastics, PVC etc.
- Label Patching Printing
- Ticket Printing
- Business Papers



. Stacker Included in the Standard Device

. Wide-Ranging Functions

- Profitable functions like
- Integrated from Management
 - N-times format splitting
 - SPS-control

. 100% Print Control

Status-out page-control gives notice of each correctly printed page via interface

. Most Low-Priced Cold Fuser at the Market

. SAP-AND AS/400 - Compatible

The low operating costs are well as the low cost price make the CF40 the most economic printer of this class of performance.
The cold fusing via Xenon-flash lamps enables the manufacturing of thermis sensitive media. Even on thick material the fusing takes place without any problems.


Print Engine

Print technology	LED, OPC Xenon-flash lamp
Controller	MPC 3.x with Intel CPU (>2 GHz CISC Prozessor)
Print speed	2000 lpm (6 lpi) up to 40 pages/minute (A4 landscape) 8,4 m/min
Resolution	max. 600 dpi x 600 dpi
Recommended monthly print volume	up to 300.000 pages (based on a using period of 60 months)
Power supply	230V +/-10% /50 Hz max 3,0 kVA (delivery with 16Amp. connector) CEE Stecker)
Acoustic noise (stand-by)	< 55 dB (A)
Dimensions(WxDxH in mm)	805 x 850 x 1250
Weight	274 kg
Environment	relative humidity 30 - 80 % temperature 10 - 30°C
Interfaces	serial USB 2.0 parallel IEEE 1284 network Ethernet-Interface 10/100 Mbit, bi-direktional (TCP/IP)
Memory	RAM 512 MB Flash 64 MB

MPC 3.x High-End Print-Controller

Emulations	MICROPLEX IDOL HP PCL 5e Epson FX-80	IBM Proprinter Diablo 630 μ-Postscript TIFF
Optional Emulations	Printronix IGP PGL, ZPLII Datamax, EPL	Magnum Code V Kyocera Prescribe Express IPDS (more emulations on request)
Barcodes	EAN 8, 13, 128, add on 2/5 3-stroke Datalogic 2/5 3-stroke Matrix Codabar, PDF 417 Royalbar, Planet	Jetcaps (HP/SAP) Code 39 128 MSI UPC A, E Postnet, KIX USPS One Code
Optional Barcodes	USD5 Aztec-Code	UPS-Maxicode Datamatrix (more barcodes on request)
Functions	Intelligent barcode generation on-the-fly in the printer Format splitting in several subformats by command. Integrated form management up to 12 MB flash for forms and fonts inside the printer	
Optional Functions	Status-Out .gives notice of each correctly printed page via interface SPS-Control Integration of the printer into production lines is possible, controlled by SPS interface.	

Paper Path



Feeder/Stacker

Input	push tractor
Output	stacker capacity: 3.000 pages (at 64 g/m²)

Media

Size	form length with stacker	7" - 24" 8" - 14"
	form width printable area	6,5" - 16" 14,6"
Weight		60 - 204 g/m²